Application No.: 10/731513 Docket No.: DC7006USNA

Page 2

## Amendments to Claims

## What is Claimed is:

- 1. [Currently amended] A multilayered article comprising a plurality of layers of polyamides and arranged to include two surface layers and one or more inner layers, and wherein said surface layers further comprise one or more aliphatic polyamides wherein the aliphatic polyamides contain one or more oxidation stabilizers and wherein at least one of said inner layers comprises a semi-aromatic polyamide derived from at least about 25 mole percent of aromatic monomers wherein the semi-aromatic polyamide does not contain oxidation stabilizers.
- [Currently amended] The multilayered article of claim 1 wherein said [aliphatic
  polyamides further comprise one or more] oxidation stabilizers <u>are</u> selected from
  the group consisting of copper saits, aromatic amines, and hindered phenols.
- [Original] The multilayered article of claim 1 wherein said aliphatic polyamides have melting points below 280 °C.
- 4. [Original] The multilayered article of claims 1 or 2 in the form of a tube.
- 5. [Original] A heat exchanger incorporating the multilayered article of claims 1 or 2 in the form of a tube.
- 6. [Withdrawn] A process for the manufacture of a multilayered article comprising a plurality of layers of polyamides and arranged to include two surface layers and one or more inner layers, and wherein said surface layers further comprise one or more aliphatic polyamides and wherein at least one of said inner layers comprises a semi-aromatic polyamide derived from at least about 25 mole percent of aromatic monomers, comprising:
  - (a) melt-extruding each of said plurality of layers of polyamides under processing conditions suitable for each layer, and thereafter

APR. 18. 2006 11:48AM

NO. 3482 P. 5

Application No.: 10/731513 Docket No.: DC7006USNA

Page 3

- (b) combining said layers into a selected multilayered configuration.
- 7. [Withdrawn] The process of claim 5 wherein said aliphatic polymers further comprise one or more oxidation stabilizers selected from the group consisting of copper salts, aromatic amines, and hindered phenols.
- 8. [Withdrawn] The process of claims 5 or 6 further comprising the step (c) of annealing said selected multilayered configuration.